





ACS HIGH TEMP GRILL CLEANER

ACS HIGH TEMP GRILL CLEANER will cut back your flattop grill downtime by enabling grill cleaning while hot, from 325°F to 475°F. Strip grease build-up in 1 minute, and ensure fresh use without rinsing.

DIRECTIONS FOR USE

Directions for Use:

- Turn off grill & empty grease troughs and pans. Scrape off loose burned soils.
- 2. While grill is hot (325°F-475°F), spread thin coat over grill surface and let set for 1 minute.
- 3. Gently scrub grill surface. Reapply as needed to liquify all soils.
- 4. Squeegee solution off grill into grease trough and wipe surface with a damp cloth.
- 5. Re-season grill with thin coat of fresh oil.
- 6. Clean grease trough with degreaser before replacing.
- Clean outer grill areas with degreaser, avoiding grill surface.

GENERAL PRODUCT INFORMATION

Description: Ready-to-Use Grill Cleaner

Safety: Corrosive. Keep product stored in original container, in an upright position, with container tightly closed. Wear protective clothing, gloves, and eye and face protection. If swallowed, rinse mouth - Do Not induce vomiting. If on skin, wash with water - remove contaminated clothing. If inhaled, remove person to fresh air - administer artificial respiration if not breathing. If in eye, flush eye continuously with water - remove contacts and continue flushing with water. Seek medical assistance if symptoms persist. Dispose of contents/container according to local/ regional regulations.

For Chemical Emergency, spill, leak, fire, exposure, or accident, contact: Chemtrec (day or night) - Within USA and Canada - 1-800-424-9300.

Packaging: Net Contents: 1 Qt. (.95L); Case Contents: 6/1 Quarts (5.7L)

Product #: 12001260

See Safety Data Sheet (SDS) for a complete listing of hazards, precautions, first aid statements, storage and handling information.

AMERICAN CHEMICAL SYSTEMS

Manufactured by:



AMERICAN CHEMICAL SYSTEMS II, LLC

2520 South Sheridan St. Wichita, Kansas 67217 • 800-889-3489

http://americanchemicalsystems.com/

^{*}Please consult your ACS sales Representative or call 1-800-889-3489 for additional use directions.